




CS 149

Professor: Alvin Chao

CS149 – Nested Loops





Loops and Scope

- Reminder – the **scope** of a variable is the part of the program where that variable is visible
- Will this compile?

```
while (number < 10) {  
    String result = "latest " + number;  
    number++;  
}  
System.out.println(result);
```



Loops and Scope

- Reminder – the **scope** of a variable is the part of the program where that variable is visible
- Will this compile?

```
while (number < 10) {  
    String result = "latest " + number;  
    number++;  
}  
System.out.println(result);
```

- No! result only exists in the block where it was declared



Loops and Scope

- Notice the difference between these loops

```
int i;  
for (i = 0; i < 10; i++) {  
    // Do some things.  
}
```

```
for (int i = 0; i < 10; i++) {  
    // Do some things.  
}
```



Loops and Scope

- Notice the difference between these loops

```
int i;  
for (i = 0; i < 10; i++) {  
    // Do some things.  
}
```

```
for (int i = 0; i < 10; i++) {  
    // Do some things.  
}
```

- What will be printed?

```
int i;  
for (i = 0; i < 10; i++) {  
    // Do some things.  
}  
System.out.println(i);
```

```
for (int i = 0; i < 10; i++) {  
    // Do some things.  
}  
System.out.println(i);
```



Loops and Scope

- Notice the difference between these loops

```
int i;  
for (i = 0; i < 10; i++) {  
    // Do some things.  
}
```

```
for (int i = 0; i < 10; i++) {  
    // Do some things.  
}
```

- What will be printed?

```
int i;  
for (i = 0; i < 10; i++) {  
    // Do some things.  
}  
System.out.println(i);
```

```
for (int i = 0; i < 10; i++) {  
    // Do some things.  
}  
System.out.println(i);
```



Quiz #1

- What will be printed when this code executes?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
}
```



Quiz #1

- What will be printed when this code executes?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
}
```

0
1
2



Quiz #2

- What will be printed when this code executes?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; j++) {  
        System.out.printf(">>%d %d\n", i, j);  
    }  
}
```

Quiz #2

- What will be printed when this code executes?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; j++) {  
        System.out.printf(">> %d %d\n", i, j);  
    }  
}
```

- This is a nested loop.

```
0  
>> 0 0  
>> 0 1  
1  
>> 1 0  
>> 1 1  
2  
>> 2 0  
>> 2 1
```



Quiz #3

- What will be printed when this code executes?

```
for (int i = 0; i < 2; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; j++) {  
        System.out.printf("--%d %d\n", i, j);  
    }  
  
    for (int k = 0; k < 3; k++) {  
        System.out.printf("**%d %d\n", i, k);  
    }  
}
```



Quiz #3

- What will be printed when this code executes?

```
for (int i = 0; i < 2; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; j++) {  
        System.out.printf("-- %d %d\n", i, j);  
    }  
  
    for (int k = 0; k < 3; k++) {  
        System.out.printf("** %d %d\n", i, k);  
    }  
}
```

0
-- 0 0
-- 0 1
** 0 0
** 0 1
** 0 2
1
-- 1 0
-- 1 1
** 1 0
** 1 1
** 1 2



Quiz #4

- What will be printed when this code executes?
- Be careful!

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = i; j < 2; j++) {  
        System.out.printf("--%d %d\n", i, j);  
    }  
}
```



Quiz #4

- What will be printed when this code executes?
- Be careful!

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = i; j < 2; j++) {  
        System.out.printf("-- %d %d\n", i, j);  
    }  
}
```

0
-- 0 0
-- 0 1
1
-- 1 1
2



Naming Index Variables

- Why “i” and “j”? Aren't we supposed to pick meaningful names?
- Yes, but i and j are a widely used conventions for cases where:
 - We are only using the variable to keep track of how many times the loop has executed
 - We are using the variables to “i”ndex into some sequence...



Naming Index Variables

```
public static int countX(String word) {  
    int count = 0;  
  
    for (int i = 0; i < word.length(); i++) {  
        if (word.charAt(i) == 'X') {  
            count++;  
        }  
    }  
    return count;  
}
```



Why Nested Loops

- Example of a nested loop in practice:

```
public static void listPrimes(int max) {  
    boolean noDivisors;  
  
    for (int candidate = 2; candidate <= max; candidate++) {  
        noDivisors = true;  
  
        // Check the current candidate for primality  
        for (int divisor = 2; divisor <= Math.sqrt(candidate); divisor++) {  
            if (candidate % divisor == 0) {  
                noDivisors = false;  
            }  
        }  
        // If there were no divisors, it must be prime. Print it.  
        if (noDivisors) {  
            System.out.println(candidate);  
        }  
    }  
}
```



Common Mistake

- See any problems?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; i++) {  
        System.out.printf(">> %d %d\n", i, j);  
    }  
}
```



Common Mistake

- See any problems?

```
for (int i = 0; i < 3; i++) {  
    System.out.println(i);  
  
    for (int j = 0; j < 2; i++) {  
        System.out.printf(">> %d %d\n", i, j);  
    }  
}
```

i is incremented here
instead of j. Probably a
copy-paste error.





Any Problems With This Method?

```
public static boolean hasRepeatedCharacter(String word) {  
  
    for (int i = 0; i < word.length(); i++) {  
        for (int j = 0; j < word.length(); j++) {  
            if (word.charAt(i) == word.charAt(j)) {  
                return true;  
            }  
        }  
    }  
    return false;  
}
```



Any Problems With This Method?

```
public static boolean hasRepeatedCharacter(String word) {  
  
    for (int i = 0; i < word.length(); i++) {  
        for (int j = 0; j < word.length(); j++) {  
            if (word.charAt(i) == word.charAt(j)) {  
                return true;  
            }  
        }  
    }  
    return false;  
}
```

- Two reasonable answers:
 - Multiple return statements violate the style guide. (OK with me in this case.)
 - Doesn't work correctly.

Fixed

```
public static boolean hasRepeatedCharacter(String word) {  
  
    for (int i = 0; i < word.length(); i++) {  
        for (int j = i + 1; j < word.length(); j++) {  
            if (word.charAt(i) == word.charAt(j)) {  
                return true;  
            }  
        }  
    }  
  
    return false;  
}
```

- Now it compares every letter to all of the subsequent letters.



- **Acknowledgements**

Parts of this activity are based on materials developed by Chris Mayfield and Nathan Sprague.

</end>